

UCA Series

Coin Acceptor

- Low power consumption
- Eight coin channels available at once.
- Mechanical and electrical anti-string functions.
- Accepting speed up to 3 coins per second.
- Coin sorter option available for UCA1,UCA2 and UCAES .



ict


UCA Series

Coin Acceptor

UCA series is designed as reliable coin acceptors which are able to work steadily in high temperature for high-security with acceptance rate up to 96% or greater.

Moreover, UCA Series includes UCA1, UCA2, UCA3, UCAE and UCAES for different accepted coins and applications to fulfill your needs.

Specifications

 Acceptance Rate 96% or greater	 Power Consumption Standby : 0.05A, 0.6W Operation: 0.2 A, 2.4W Maximum: 0.5 A, 6 W
 Acceptance Speed Approx. 3 coins/sec.	 Dimension 147.5 x 72.4 x 124 mm/ 14.55 x 5.81 x 4.88inches
 Interface Pules, RS232 (TTL level)	 Weight Approx. 0.35 kg/0.77 lbs
 Coin Parameters Diameter : 20~32 mm/0.78~1.25 inches Thickness: 1.2~3.2 mm/0.05~0.13 inches	 Environmental Operating Temperature: -5°C~60°C Storage Temperature : -20°C~75°C Humidity: 30% ~ 85%RH (no condensation)
 Power Source 12V ± 10% (10.8V ~ 13.2V DC)	 Recommended Applications Indoor/Vending, Kiosk, Amusement

Specifications are subject to change without prior notice.



International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihs Dist., Taipei City 114, Taiwan (R.O.C.)

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email : sales@ictgroup.com.tw (Product Information)

rma@ictgroup.com.tw (Technical Service)

Website : www.ictgroup.com.tw

